

**PS-3315 Spec Sheet**

<b>System Configuration</b>	
Processor	Intel Celeron N2807 processor, 1.58GHz/2.16GHz (Burst), 1M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 4GB
Storage Device	2 x SATA Port (1 x SATA + 1 x mSATA) + 1 x eMMC connector
Power Supply	12V / 60W
OS support	Windows 7 / POSReady 7 / Windows Embedded 8.1 Industry / Linux per request
<b>Display &amp; Touch</b>	
LCD	15" TFT LCD
Resolution	1024 x 768
Touch	5-wire resistive touch
<b>I/O &amp; Expansion</b>	
Serial Port	3 x DB9 + 1 x RJ50, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
Standard USB Port	5
Powered USB Port	Optional 24V x 1 + 12V x 3 via GEN8E base
LAN Port	10 / 100 / 1000 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	1, via optional conversation cable
UPS Port	N/A

Audio	Buzzer only
Internal Expansion Slot	N/A
<b>Environmental</b>	
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

**Note 1-** Please note that this specification is pre-production spec, and is subjected to change without notice

**Note 2-** eMMC support requires WE 8.1 Industry; when eMMC functions as the boot device, it does not work with other SATA device(s)