

XT-3015



| | |
|----------------|---|
| Specification | XT-4015 |
| Processor | Intel Pineview dual core D525 CPU, 1.8GHz, 1M Cache |
| System Memory | DDR3 800MHz, SO-DIMM x 1, max. 4GB, factory default 2GB |
| Storage Device | SATA storage x 2; Factory default 320GB HDD x 1 |
| Power Supply | 12V DC power adaptor, 60W (Optional 80W when equipping with 2nd LCD display LM-3014 & LM-3015) |
| OS Support | Windows 7/POSReady 7/Windows XP Pro/POSReady 2009/Windows Embedded 8.1 Industry / Linux per request |

| | |
|-------------------|--|
| Connectivity | |
| LAN Port | 10/100/1000Mb x 2 |
| Serial Port | DB9 x 3 + RJ45 x 1 with 5V/12V support on COM1 / COM2 / COM3 / COM4, RJ-45 to DB9 cable optional |
| UPS Port | Yes |
| Standard USB Port | 5 (2 x USB 3.0/2.0 + 3 x USB 2.0) |
| CR Port | 1, control 2 CR |
| VGA Port | D-USB, 15pins, with 12V support for Posiflex monitor |
| CR Port | 1, control 2 CR |
| Mini-PCIe slot | Yes, for half size card |

| | |
|-----------------|---|
| Display & Touch | |
| LCD | 15" TFT LCD |
| Resolution | 1024 x 768 |
| Touch | Bezel-free Projected Capacitive Touch (IP65 on front panel) |

| | |
|-----------------------------|-------------------|
| Physical Dimension | |
| Dimension (W x D x H in mm) | 372 x 320 x 252.7 |
| Weight (N.W. in Kg) | 5.6 |

| | |
|---------------------|---|
| Environment | |
| Operation Condition | 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) |
| Storage Condition | -20°C - 70°C, 10%RH - 90%RH |

| | |
|-----------|---|
| Options | |
| SSD | 8GB minimum |
| SA-105 | Side Attachment for XT Series with 3 track MSR |
| SA-205 | Side Attachment for XT Series with iButton |
| SA-305 | Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor |
| SA-405 | Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor |
| LM-3010 | 9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface) |
| LM-3014 | 14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface) |
| LM-3015 | 15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface) |
| LM-6607 | 7" 800 x 480 rear-mount 2nd display for XT series (USB interface) |
| TM-3010 | 9.7" 1024 x 768 rear-mount resistive touch display for XT Series (VGA interface) |
| TM-3014 | 14" 1366 x 768 rear-mount resistive touch display for XT Series (VGA interface) |
| TM-3015 | 15" 1024 x 768 rear-mount resistive touch display for JIVA XT Series (VGA interface) |
| PD-2608UE | 2 x 20 VFD, rear-mount, USB with Virtual COM support |
| PD-350UE | 2 x 20 LCD, rear-mount, USB with Virtual COM support |
| PD-6607 | 7" color LCD graphical line display, rear-mount (USB interface) |
| WIFI | External USB dongle or internal mini-PCIe module |

* The product information and specifications are subject to change without prior notice.
 * Please refer to the web site for more attachment options.



Design and Manufacturing in Taiwan by Posiflex Technology Inc.
 The product information and specifications are subject to change without prior notice.

2015Q1



POSIFLEX TECHNOLOGY INC.
 No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
 Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
 Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller



Flexible! Powerful! Elegant!

XT-3015

Fan-free POS Terminal



In today's retail and hospitality market, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of the customers.

With a bezel free Projected capacitive touch screen, beautifully sculptured slim body, sexily curved base stand, XT-3015 Series looks right at home at any elegantly decorated store. And more than just good looks, JIVA XT Series also offers ample of performance and flexibility to satisfy the most demanding of daily POS operations

Flexibility

XT-3015 series comes with the selection of two newly designed foldable bases, the curvy slim 7th Generation Base and the larger but practical 8th Generation Base.

The new foldable base allows XT-3015 Series to be configured into different configurations. "Flat Folded Mode" to save the shipping package volume. "Low Profile Mode" to allow greater interaction between cashier and the customers; and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever. This one terminal/multi-configurations concept provides unmatched flexibility to store owners and system integrators alike.



Full Extended Mode



Low Profile Mode



Flat Folded Mode

Looks

XT-3015 Series is the first to come from new Posiflex design language. Slimmer and sexier than ever, it is a sharp departure from the traditionally more conservative Posiflex terminal design. Every curves and details are carefully thought out to make XT-3015 Series one of the most visually desirable terminals in the market.



Dual LAN

XT-3015 Series provides dual LAN ports that allow a dedicated LAN connection for credit card terminal.



8th Generation Base

Optional 8th Generation Base that integrates internal power adaptor and Powered USB port into the base stand, which allows for clutter free counter.